according to Regulation (EC) No. 1907/2006, (EC) 2015/830



Duparol

Version 2.0 Revision Date 09.03.2017 Print Date 10.03.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Duparol

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Protective coating

stance/Mixture

Recommended restrictions

on use

: within adequate application - none

1.3 Details of the supplier of the safety data sheet

Company : Caparol Farben Lacke GmbH

Roßdörfer Straße 50 64372 Ober-Ramstadt

Telephone : +496154710
Telefax : +49615471222
E-mail address Responsi- : msds@dr-rmi.com

ble/issuing person

1.4 Emergency telephone number

Emergency telephone num: +49615471202

ber 1

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flam. Liq. 3 H226: Flammable liquid and vapour.

STOT SE 3, Central nervous system H336: May cause drowsiness or dizziness.

STOT RE 1 H372: Causes damage to organs through pro-

longed or repeated exposure.

Aquatic Chronic 3 H412: Harmful to aquatic life with long lasting ef-

fects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

according to Regulation (EC) No. 1907/2006, (EC) 2015/830

Duparol

Version 2.0 Revision Date 09.03.2017 Print Date 10.03.2017

Hazard pictograms







Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness. H372 Causes damage to organs through pro-

longed or repeated exposure.

H412 Harmful to aquatic life with long lasting ef-

fects.

Supplemental Hazard

Statements

EUH066

Repeated exposure may cause skin dry-

ness or cracking.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smoking.

P260 Do not breathe vapours/ spray.

P262 Do not get in eyes, on skin, or on clothing.
P271 Use only outdoors or in a well-ventilated

area.

P273 Avoid release to the environment.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immedi-

ately all contaminated clothing. Rinse skin

with water/shower.

Hazardous components which must be listed on the label:

Naphtha (petroleum), hydrodesulfurized heavy

Additional Labelling

EUH208 Contains Fatty acids, C18-unsatd., dimers, reaction products with N,N-dimethyl-1,3-propanediamine and 1,3-propanediamine. May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Restricted to professional users.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Polymer resin paint, solvent-containing

Hazardous components

OL	OAO NI	01"	0
Chemical name	CAS-No.	Classification	Concentration

according to Regulation (EC) No. 1907/2006, (EC) 2015/830

Duparol

Version 2.0 Revision Date 09.03.2017 Print Date 10.03.2017

	EC-No.		(% w/w)
	Registration number		,
Naphtha (petroleum), hydrodesul- furized heavy	64742-82-1 265-185-4 01-2119484809-19- XXXX, 01- 2119458049-33- XXXX, 01- 2119490979-12- XXXX, 01- 2119473977-17- XXXX, 01- 2119458049-33- XXXX, 01- 2119463586-28- XXXX	Flam. Liq. 3; H226 STOT SE 3; H336 Asp. Tox. 1; H304 Aquatic Chronic 2; H411 STOT RE 1; H372	>= 10 - < 20
Solvent naphtha (petroleum), light arom.	64742-95-6 265-199-0 01-2119455851-35- XXXX, 01- 2119455851-35- XXXX	STOT SE 3; H335, H336 Aquatic Chronic 2; H411 Flam. Liq. 3; H226	>= 2,5 - < 5
Carbamidharz	Not Assigned	Aquatic Chronic 3; H412	>= 1 - < 2,5
Fatty acids, C18-unsatd., dimers, reaction products with N,N-dimethyl-1,3-propanediamine and 1,3-propanediamine	162627-17-0	Skin Sens. 1; H317	>= 0,1 - < 1
Substances with a workplace expos	sure limit :		
Naphtha (petroleum), hydrotreated heavy	64742-48-9 265-150-3 01-2119463258-33- XXXX, 01- 2119457273-39- XXXX	Flam. Liq. 3; H226 STOT SE 3; H336 Asp. Tox. 1; H304	>= 5 - < 10
Kieselguhr, soda ash flux-calcined	68855-54-9 272-489-0 21-2119488518-22- XXXX		>= 5 - < 10

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : No hazards which require special first aid measures.

If inhaled : If breathed in, move person into fresh air.

If breathing is irregular or stopped, administer artificial respira-

tion.

If unconscious, place in recovery position and seek medical

according to Regulation (EC) No. 1907/2006, (EC) 2015/830

Duparol

Version 2.0 Revision Date 09.03.2017 Print Date 10.03.2017

advice.

In case of skin contact Take off all contaminated clothing immediately.

Wash skin thoroughly with soap and water or use recognized

skin cleanser.

Do NOT use solvents or thinners.

: Remove contact lenses. In case of eye contact

If swallowed If swallowed, DO NOT induce vomiting.

> If accidentally swallowed obtain immediate medical attention. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Risks No information available.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Cool closed containers exposed to fire with water spray. In case of fire hazardous decomposition products may be

produced such as:

Carbon monoxide, carbon dioxide and unburned hydrocar-

bons (smoke).

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment. :

Treat recovered material as described in the section "Disposal

considerations".

6.2 Environmental precautions

Environmental precautions Prevent product from entering drains.

according to Regulation (EC) No. 1907/2006, (EC) 2015/830

Duparol

Version 2.0 Revision Date 09.03.2017 Print Date 10.03.2017

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Suitable cleaning agents

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see

section 8).

Avoid inhalation, ingestion and contact with skin and eyes.

Keep away from heat and flame. Keep away from fire (No Smoking). Keep away from flames and sparks.

Advice on protection against :

fire and explosion

Normal measures for preventive fire protection.

Hygiene measures : Avoid contact with the skin and the eyes. Ensure adequate

ventilation, especially in confined areas. Wash hands before

eating, drinking, or smoking.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Store between 5 and 25 °C in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Store in original container. Keep containers tightly closed in a dry, cool and well-ventilated place. Observe label precautions.

Storage class (TRGS 510) : 3, Flammable liquids

7.3 Specific end use(s)

Specific use(s) : Please follow the technical information of the manufacturer.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Naphtha (petrole- um), hydrotreated heavy	64742-48-9	AGW	200 ml/m3	DE TRGS 900
		AGW	1.500 mg/m3	DE TRGS 900

according to Regulation (EC) No. 1907/2006, (EC) 2015/830

Duparol

Version 2.0 Revision Date 09.03.2017 Print Date 10.03.2017

Peak-limit: excursion factor (category)	2;(II)				
Further information	Group exposure limit for hydrocarbon solvent mixtures, Commission for dangerous substances, See also No. 2.9 of the TRGS 900				
	gerous substa	AGW	600 mg/m3	DE TRGS 900	
Peak-limit: excursion factor (category)	2;(II)				
Further information	Group exposure limit for hydrocarbon solvent mixtures, Commission for dangerous substances, See also No. 2.9 of the TRGS 900				
Naphtha (petrole- um), hydrodesulfu- rized heavy	64742-82-1	AGW	100 ml/m3	DE TRGS 900	
,		AGW	100 mg/m3	DE TRGS 900	
Peak-limit: excursion factor (category)	2;(II)				
Further information	Group exposure limit for hydrocarbon solvent mixtures, Commission for dangerous substances, See also No. 2.9 of the TRGS 900				
Solvent naphtha (petroleum), light arom.	64742-95-6	AGW	50 ml/m3	DE TRGS 900	
		AGW	100 mg/m3	DE TRGS 900	
Peak-limit: excursion factor (category)	2;(II)				
Further information	Group exposure limit for hydrocarbon solvent mixtures, Commission for dangerous substances, See also No. 2.9 of the TRGS 900				
Kieselguhr, soda ash flux-calcined	68855-54-9	AGW (Alveolate fraction)	0,3 mg/m3	DE TRGS 900	
Further information	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission)., Diatomeous earth can, depending on its origin, contain quartz. The calcining of silica leads to a higher content of cristobalite, activated silica can contain up to 60 vol.% cristobalite. In examining the exposure to (calcined) silica both the amorphous part (limit value for diatomeous earth resp. calcined silica) and the total of the cristobalite and quartz content (carcinogenic according to TRGS 906) should be established., When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child				

8.2 Exposure controls

Engineering measures

Handle only in a place equipped with local exhaust (or other appropriate exhaust).

Personal protective equipment

Eye protection : Tightly fitting safety goggles

German trade association rules - BGR 192 Eye protection

Hand protection

Material : Nitrile rubber Glove thickness : 0,2 mm Protective index : Class 3

Remarks : Before removing gloves clean them with soap and water.

according to Regulation (EC) No. 1907/2006, (EC) 2015/830

Duparol

Version 2.0 Revision Date 09.03.2017 Print Date 10.03.2017

Wear suitable gloves tested to EN374.

Skin and body protection : impervious clothing

Choose body protection according to the amount and concen-

tration of the dangerous substance at the work place.

Respiratory protection : No personal respiratory protective equipment normally re-

quired.

Respiratory protection : German trade association rules - BGR 190 Breathing protec-

tion

Protective measures : Follow the skin protection plan.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : No data available

Odour : solvent-like

Odour Threshold : Not relevant

pH : not determined

Melting point/freezing point : not determined

Boiling point/boiling range : not determined

Flash point : 40 °C

Evaporation rate : Not applicable

Flammability (solid, gas) : Sustains combustion

Upper explosion limit : not determined

Lower explosion limit : not determined

Vapour pressure : not determined

Relative vapour density : not determined

Relative density : not determined

Density : 1,3000 g/cm3

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

not determined

Auto-ignition temperature : not determined

Decomposition temperature : Not applicable

Viscosity

according to Regulation (EC) No. 1907/2006, (EC) 2015/830

Duparol

Version 2.0 Revision Date 09.03.2017 Print Date 10.03.2017

Viscosity, kinematic : > 21 mm2/s (40 °C)

Method: ISO 3104/3105

Flow time : 90,0 s

Cross section: 4 mm Method: DIN 53211

Explosive properties : Not applicable

Oxidizing properties : Not applicable

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended storage conditions.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if used as directed.

10.4 Conditions to avoid

Conditions to avoid : Protect from frost, heat and sunlight.

10.5 Incompatible materials

Materials to avoid : Incompatible with oxidizing agents.

Incompatible with acids and bases.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Components:

Solvent naphtha (petroleum), light arom.:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg

Method: OECD Test Guideline 402

according to Regulation (EC) No. 1907/2006, (EC) 2015/830

Duparol

Version 2.0 Revision Date 09.03.2017 Print Date 10.03.2017

Skin corrosion/irritation

Product:

Remarks: May cause skin irritation in susceptible persons.

Serious eye damage/eye irritation

Product:

Remarks: According to the classification criteria of the European Union, the product is not considered as being an eye irritant.

Respiratory or skin sensitisation

Product:

Remarks: Repeated contact may cause allergic reactions in very susceptible persons.

Further information

Product:

Remarks: No data available

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: No data is available on the product itself.

aquatic invertebrates

Toxicity to daphnia and other : Remarks: No data is available on the product itself.

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: No data available

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available

12.4 Mobility in soil

Product:

Remarks: No data available Mobility

12.5 Results of PBT and vPvB assessment

Product:

Assessment This substance/mixture contains no components considered

> to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

according to Regulation (EC) No. 1907/2006, (EC) 2015/830

Duparol

Version 2.0 Revision Date 09.03.2017 Print Date 10.03.2017

0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic organisms, may cause long-term adverse

effects in the aquatic environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Materials and all related packaging must be disposed of in a

safe way in accordance with the full requirements of the local,

regional, national and international authorities.

Contaminated packaging : Only completely emptied containers should be given for recy-

cling.

Waste Code : used product

080111, waste paint and varnish containing organic solvents

or other dangerous substances

SECTION 14: Transport information

14.1 UN number

ADN : UN 1263
ADR : UN 1263
RID : UN 1263
IMDG : UN 1263
IATA : UN 1263

14.2 UN proper shipping name

ADN : PAINT

(low boiling point hydrogen treated naphtha, low boiling point

hydrogen treated naphtha)

ADR : PAINT

(low boiling point hydrogen treated naphtha, low boiling point

hydrogen treated naphtha)

RID : PAINT

(low boiling point hydrogen treated naphtha, low boiling point

hydrogen treated naphtha)

IMDG : PAINT

(low boiling point hydrogen treated naphtha, low boiling point

hydrogen treated naphtha)

IATA : Paint

(low boiling point hydrogen treated naphtha, low boiling point

according to Regulation (EC) No. 1907/2006, (EC) 2015/830

Duparol

Version 2.0 Revision Date 09.03.2017 Print Date 10.03.2017

hydrogen treated naphtha)

14.3 Transport hazard class(es)

ADN : 3
ADR : 3
RID : 3
IMDG : 3
IATA : 3

14.4 Packing group

ADN

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

ADR

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)

Remarks : Special Provision 640E

Packages smaller than or equal to 450 litres, not

goods/merchandise of Class 3

RID

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

IMDG

Packing group : III Labels : 3

EmS Code : F-E, <u>S-E</u>

Remarks : Packages smaller than or equal to 30 litres, not

goods/merchandise of Class 3

IATA (Cargo)

Packing instruction (cargo : 366

aircraft)

Packing instruction (LQ) : Y344
Packing group : III

Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passen- : 355

ger aircraft)

Packing instruction (LQ) : Y344
Packing group : III

Labels : Flammable Liquids

14.5 Environmental hazards

ADN

according to Regulation (EC) No. 1907/2006, (EC) 2015/830

Duparol

Version 2.0 Revision Date 09.03.2017 Print Date 10.03.2017

Environmentally hazardous : no

ADR

Environmentally hazardous : no

rid

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

Remarks : see sections 6-8

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P5c PLAMMABLE LIQUIDS Quantity 1 Quantity 2 50.000 t 50.000 t

34 Petroleum products: (a) 2.500 t 25.000 t

gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

Water contaminating class

(Germany)

2 significantly water endangering

Classification according to AwSV, Annex 1 (5.2)

Product code for laquers and

paints / Giscode

: M-PL02 Polymer resin paints, low in aromatics

Volatile organic compounds : Directive 2004/42/EC

< 33 % 420 g/l

Other regulations : Take note of Directive 92/85/EEC regarding maternity protec-

tion or stricter national regulations, where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applica-

ble.

according to Regulation (EC) No. 1907/2006, (EC) 2015/830

Duparol

Version 2.0 Revision Date 09.03.2017 Print Date 10.03.2017

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

SECTION 16: Other information

Full text of H-Statements

H226 : Flammable liquid and vapour.

H304 : May be fatal if swallowed and enters airways.

H317
H335
H336
May cause an allergic skin reaction.
May cause respiratory irritation.
May cause drowsiness or dizziness.

H372 : Causes damage to organs through prolonged or repeated

exposure.

H411 : Toxic to aquatic life with long lasting effects.
H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Chronic : Chronic aquatic toxicity
Asp. Tox. : Aspiration hazard
Flam. Liq. : Flammable liquids
Skin Sens. : Skin sensitisation

STOT RE : Specific target organ toxicity - repeated exposure STOT SE : Specific target organ toxicity - single exposure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Ari Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; ICSO - Half maximal inhibitory concentration; ICAO - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; ICSO - Half maximal inhibitory concentration; ICAO - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals In Bulk; ICSO - Half maximal inhibitory concentration; ICAO - International Maritime Organization; IECSC - Inventory of Existing Chemicals Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Dangerous Goods; IMO - International Maritime Organization; IECSC - International Maritime Organization for Standardization; KECI - Korea Existing Chemicals Inventory; ICSO - Lethal Concentration to 50 % of a test population; LDSO - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.

Further information

Other information:

No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC.

This product is a mixture and does not contain Substances of Very High Concern (SVHC) equal or above 0.1%. Therefore no advised uses have to be defined and no chemical safety assessment has to be generated.

Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific

according to Regulation (EC) No. 1907/2006, (EC) 2015/830

Duparol

Version 2.0 Revision Date 09.03.2017 Print Date 10.03.2017

material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly. This will be put into practice depending on the register-deadline of the substances involved during the transition period from December 1, 2010 till May 31, 2018.

DE / EN